



Model			HLM1250 RT
TRACTION SYSTEM			4 INDEPENDENT MOTOR WHEELS
Wheelbase	Extendable	mm	7.000 - 9.000
Tyres	Size front/rear	ins	24.00 -35 / 24.00 -35
Lifting Capacity (see load chart)		kg	140.000
Load Centre		mm	1.874
Lifting height		mm	17.750
Overall dimension	Lenght	mm	9.800 - 11.800
	Width	mm	6.500
	Height	mm	5.400
	boom height, Max.	mm	18.850
Turning Radius	outer	mm	12700
Stability (static)			EN 1459
Speed	Traveling F. R. Laden/unladen		8 / 16
	Lifting : laden / unladen 1800 rpm	m/s	0,24 / 0,58
	Lowering laden / unladen 1800 rpm	m/s	0,42 / 0,42
Gradeability	max at 0 km /h - laden	%	16%
Gross vehicle weight	without attachment	kg	97.000
Axle load - Front	unladen	kg	39.300
Axle load - rear	unladen	kg	57.800
Ground Clearance	Mid-way along the wheelbase	mm	490
Brake System			wet brake / driven wheels
Parking breake			spring brake
Steering System			hydrostatic
Engine	manufacturer type		VOLVO TAD1170 EURO IV
Fuel Consumption (average)		l/h	8 / 12
Trasmission System			hydrostatic
	N° forward and reverse gears	n°	hydrostatic continuous
Front/Rear Axle Type			CES CUSTOMIZE / CES CUSTOMIZE
CABIN			Cabin centrally positioned
			Noise emission according EN 12053
			Automatic air condition
Sound Level	inside cabin		68 dB (A)
Hydraulic system			load sensing Bosh Rexroth
N° pump hydraulic system		n°	2
Pressure		bar/max	330
Hydraulic pump max flow rate		l/m	500
N° pump hydrostatic system		n°	1
pressure		bar/max	450
Electrical system			24 volt /Can bus /Lighting led
Software control system			Electronic joystick
			Control panel LCD 8"
Lubrification			Central whit two Automotive PUMP